

225A Track Busway

1-Pole Breakered Outlet Box

Shopify SKU: T225-C-10-OB-IG520Q-G

Shopify variant ID: 43984837804119


SELECTED CONFIGURATION - PRODUCT DATA

Ordered supply	120V 1-Phase (1PNG)
Breaker protection	1 x 1-pole breaker; Selected branch current: 20A
Outputs	Quad straight blade receptacle; 5-20R
NEMA device rating	20A, 125V; 2 device poles, 3 wires including ground
Device contact roles	Line + neutral + equipment ground
Grounding	Isolated ground
CPM	None (No CPM)
Enclosure	Compact C-10
Body dimensions	9.420 W x 14.120 H x 3.860 D in. Body only; excludes projections.

ILLUSTRATION STATUS

Enclosure assembly not illustrated. The table identifies the selected configuration and body dimensions. The receptacle detail is an exact interface reference; it does not depict the complete mounted or cord-end assembly.

SELECTED RECEPTACLE REFERENCE



5-20R

NEMA 5-20R; 20A; 125V. Selected quantity: 4; Isolated ground. Female interface reference only, not a finished assembly. Source: Hubbell chart, p. IV.

T225 1-pole outlet-box | phase selection update

Order number = listed base SKU + selected phase suffix. The phase is recorded with the order.

Connection and suffix choices

Phase assignment	Order suffix	Example full order SKU
L1 to neutral	-L1	T225-C-10-OB-IG520Q-G-L1
L2 to neutral	-L2	T225-C-10-OB-IG520Q-G-L2
L3 to neutral	-L3	T225-C-10-OB-IG520Q-G-L3

Selection guidance

These suffixes apply to the listed 120V and 277V one-pole configurations.
Choose the actual phase at checkout; the base SKU alone does not record it.
Branch voltage, interface, grounding and enclosure still follow the selected base build.
A NEMA R designation names the female interface, including a cord connector body.
The OB or DCXX portion of the T225 base SKU identifies box or drop-cord style.

This page supplements the family guide. Device and complete-assembly ratings remain subject to the selected build and its marked unit; confirm feeder and phase loading.