

T225 2-pole outlet box

Standard-ground L14-30 configuration | product data

Base catalogue number

T225-S-10-OB-L1430-L1430-G

Select a phase pair on the following page to complete the order number.

Supply	208V with neutral, 1-phase (2PNG); two lines + neutral + ground
Branch protection	30A; 2-pole breaker for each selected output
Output interface	2 x NEMA L14-30 female interface; 30A, 125/250V AC
Contact roles	Two lines + neutral + equipment ground; 3 poles, 4 wires
Grounding	Standard equipment grounding; not isolated ground
Build	2 outputs; no CPM
Enclosure	Standard S-10
Body dimensions*	13.280 W x 14.620 H x 3.860 D in

Assembly and interface note

The female L14-30 interface may be supplied as a mounted receptacle or a cord connector body according to the selected factory build. The R designator identifies the interface; OB identifies the outlet-box style. No assembly drawing is shown.

Confirm the exact enclosure, connector form, device make and marked-unit ratings with USA TrackBusway before fabrication. Device interface is supported by Hubbell standard-ground L14-30 literature; it does not establish an assembly listing.

*Where shown, body dimensions follow the matching IG build; confirm fit and projections.

Reference: Hubbell/Bryant 71430FR (standard-ground L14-30R interface).

[Hubbell/Bryant 71430FR product page](#)

T225 2-pole outlet-box | phase selection update

Order number = listed base SKU + selected phase suffix. The phase is recorded with the order.

Connection and suffix choices

Phase assignment	Order suffix	Example full order SKU
L1 + L2	-L1L2	T225-S-10-OB-L1430-L1430-G-L1L2
L2 + L3	-L2L3	T225-S-10-OB-L1430-L1430-G-L2L3
L1 + L3	-L1L3	T225-S-10-OB-L1430-L1430-G-L1L3

Selection guidance

This L14 configuration includes two lines, neutral and equipment ground.
It is distinct from a two-line L6 receptacle that has no neutral contact.
The NEMA L14-30R interface does not itself specify isolated ground.
Confirm standard or isolated grounding on the completed factory build.
A NEMA R designation names the female interface, including a cord connector body.
The OB or DCXX portion of the T225 base SKU identifies box or drop-cord style.

This page supplements the family guide. Device and complete-assembly ratings remain subject to the selected build and its marked unit; confirm feeder and phase loading.