

# 225A Track Busway

## 2-Pole Breakered Outlet Box

Shopify SKU: T225-S-10-OB-L820-L820-G

Shopify variant ID: 42741716516951

SELECTED CONFIGURATION - PRODUCT DATA

|                      |                                                                    |
|----------------------|--------------------------------------------------------------------|
| Ordered supply       | 480Δ 1-Phase (2PG)                                                 |
| Breaker protection   | 2 x 2-pole breakers; Selected branch current: 20A                  |
| Outputs              | 2 receptacles; L8-20R                                              |
| NEMA device rating   | 20A, 480V AC; 2 device poles, 3 wires including ground             |
| Device contact roles | Two lines + equipment ground; no neutral                           |
| Grounding            | Standard ground                                                    |
| CPM                  | None (No CPM)                                                      |
| Enclosure            | Standard S-10                                                      |
| Body dimensions      | 13.280 W x 14.620 H x 3.860 D in. Body only; excludes projections. |

ILLUSTRATION STATUS

Enclosure assembly not illustrated. The table identifies the selected configuration and body dimensions. The receptacle detail is an exact interface reference; it does not depict the complete mounted or cord-end assembly.

SELECTED RECEPTACLE REFERENCE



L8-20R

NEMA L8-20R; 20A; 480V AC. Selected quantity: 2; Standard ground. Female interface reference only, not a finished assembly. Source: Hubbell chart, p. V.

# T225 2-pole outlet-box | phase selection update

Order number = listed base SKU + selected phase suffix. The phase is recorded with the order.

## Connection and suffix choices

| Phase assignment | Order suffix | Example full order SKU        |
|------------------|--------------|-------------------------------|
| L1 + L2          | -L1L2        | T225-S-10-OB-L820-L820-G-L1L2 |
| L2 + L3          | -L2L3        | T225-S-10-OB-L820-L820-G-L2L3 |
| L1 + L3          | -L1L3        | T225-S-10-OB-L820-L820-G-L1L3 |

## Selection guidance

This 480V L8 configuration uses two lines and equipment ground; no neutral.  
Use only the listed interface and marked unit ratings for the selected build.  
The phase pair is recorded by the order suffix shown above.  
A NEMA R designation names the female interface, including a cord connector body.  
The OB or DCXX portion of the T225 base SKU identifies box or drop-cord style.

This page supplements the family guide. Device and complete-assembly ratings remain subject to the selected build and its marked unit; confirm feeder and phase loading.