

225A Track Busway

2-Pole Breakered Outlet Box

Shopify SKU: T225-S-10-OB-L830-L830-L830-G

Shopify variant ID: 42741716877399

SELECTED CONFIGURATION - PRODUCT DATA

Ordered supply	480Δ 1-Phase (2PG)
Breaker protection	3 x 2-pole breakers; Selected branch current: 30A
Outputs	3 receptacles; L8-30R
NEMA device rating	30A, 480V AC; 2 device poles, 3 wires including ground
Device contact roles	Two lines + equipment ground; no neutral
Grounding	Standard ground
CPM	None (No CPM)
Enclosure	Standard S-10
Body dimensions	13.280 W x 14.620 H x 3.860 D in. Body only; excludes projections.

ILLUSTRATION STATUS

Enclosure assembly not illustrated. The table identifies the selected configuration and body dimensions. The receptacle detail is an exact interface reference; it does not depict the complete mounted or cord-end assembly.

SELECTED RECEPTACLE REFERENCE



NEMA L8-30R; 30A; 480V AC. Selected quantity: 3; Standard ground. Female interface reference only, not a finished assembly. Source: Hubbell chart, p. V.

T225 2-pole outlet-box | phase selection update

Order number = listed base SKU + selected phase suffix. The phase is recorded with the order.

Connection and suffix choices

Phase assignment	Order suffix	Example full order SKU
L1 + L2	-L1L2	T225-S-10-OB-L830-L830-L830-G-L1L2
L2 + L3	-L2L3	T225-S-10-OB-L830-L830-L830-G-L2L3
L1 + L3	-L1L3	T225-S-10-OB-L830-L830-L830-G-L1L3

Selection guidance

This 480V L8 configuration uses two lines and equipment ground; no neutral.
Use only the listed interface and marked unit ratings for the selected build.
The phase pair is recorded by the order suffix shown above.
A NEMA R designation names the female interface, including a cord connector body.
The OB or DCXX portion of the T225 base SKU identifies box or drop-cord style.

This page supplements the family guide. Device and complete-assembly ratings remain subject to the selected build and its marked unit; confirm feeder and phase loading.