USA TrackBusway™ 20A 45 ft Cord Reel

ETL Listed to UL 857 Busway Standards
by Intertek

Built in the United States

120V, single-phase / 1 x 1-pole / 1 x 5-20C cord-end connector

CATALOGUE NUMBER / FIXED CONFIGURATION + YOUR ORDER SELECTIONS


PT225-C-10-CR45-520C-G-[PHASE]-[T/R]

Base configuration
45 ft retractable cord

Phase connection
Select connection below

Factory orientation
Choose -T or -R


YOUR TAP-OFF CONFIGURATION



Enclosure W 9.770 in. · Overall W 11.969 in.
Assembly H 17.413 in. x D 10.841 in.

Supply	120V, single-phase
A Protection	1 x 20A, 1-pole breaker
B Output	1 x 5-20C cord-end connector
Grounding	Standard equipment ground
Enclosure	Factory reel / tap assembly
Cord length	45 ft retractable
Required SCCR	Specify with order; subject to factory confirmation
Shared branch	All outlets share one 20A branch

B CORD-END OUTPUT




5-20C

20A, 125V AC device rating
Equipment ground included
Neutral included

trackbusway.com/products/t225-45ft-breakered-cord-reel

Specify when ordering



T225 conductor arrangement

For this **120V, 1-pole** configuration, choose **one phase + neutral**.

L1 + N	L2 + N	L3 + N
Alternative	EXAMPLE	Alternative


FILL [PHASE]: L2 (example shown)

PT225-C-10-CR45-520C-G-L2-[T/R]

Reel support: threaded rod larger than 1/4 in. nominal; **1/4-20 not permitted**. Confirm support spacing and clearance.

CHOOSE THE FACTORY BREAKER ORIENTATION

Both views below show the breaker facing left. Enclosures continue below the break lines.




-T TYPICAL

CONDUCTORS / INSULATOR
LEFT side

BREAKER FACES LEFT

SAME SIDE
as the conductors



-R REVERSE

CONDUCTORS / INSULATOR
RIGHT side

BREAKER FACES LEFT

OPPOSITE SIDE
as the conductors

FACTORY-SET. NOT FIELD-ROTATABLE. Select -T or -R when ordering.

ORDERING EXAMPLES / select connection, orientation and any required cord length
Typical: PT225-C-10-CR45-520C-G-L2-T
Reverse: PT225-C-10-CR45-520C-G-L2-R

Certification reference - covered PT225 factory configurations. Intertek 5011082; Report 106508638CRT-001.

Illustrations not to scale. Body dimensions exclude projections and cord.