USA TrackBusway™ 30A PowerDrop

ETL Listed to UL 857 Busway Standards
by Intertek

Built in the United States

208V, three-phase per output / 2 x 3-pole / 2 x L21-30C cord-end connectors

CATALOGUE NUMBER / FIXED CONFIGURATION + YOUR ORDER SELECTIONS


PT225-S-10-DCXX-IGL2130C-IGL2130C-G-[T/R]

Base configuration
Cord length: specify with order

Phase connection
L1 + L2 + L3 (fixed)

Factory orientation
Choose -T or -R

YOUR TAP-OFF CONFIGURATION



Enclosure views; cord shortened

Supply	208V, three-phase per output
A Protection	2 x 30A, 3-pole breakers; one per output
B Output	2 x L21-30C cord-end connectors
Grounding	Isolated ground
Enclosure	Standard S
Body W x H x D	13.280 x 14.620 x 3.860 in.
Cord length	Specify with order
Required SCCR	Specify with order; subject to factory confirmation
Power monitoring	None

trackbusway.com/products/t225-3-pole-breakered-drop-cord


B CORD-END OUTPUT



L21-30C

30A, 120/208V AC device rating
Isolated equipment ground
Neutral included

Phase connection / specify when ordering



T225 conductor arrangement

2 independent circuits; one 30A, 3-pole breaker per output.

Cord 1
30A / 3-pole breaker
L1 + L2 + L3 + N


Cord 2
30A / 3-pole breaker
L1 + L2 + L3 + N

PHASE CONNECTION = L1L2L3 (fixed)
Each output uses all three phases. No phase entry is required.

Each output uses all three phases through its own 3-pole breaker. Equipment ground is retained; neutral is included where specified.

CHOOSE THE FACTORY BREAKER ORIENTATION

Both views below show the breaker facing left. Enclosures continue below the break lines.




-T TYPICAL

CONDUCTORS / INSULATOR
LEFT side

BREAKER FACES LEFT

SAME SIDE
as the conductors



-R REVERSE

CONDUCTORS / INSULATOR
RIGHT side

BREAKER FACES LEFT

OPPOSITE SIDE
as the conductors

FACTORY-SET. NOT FIELD-ROTATABLE. Select -T or -R when ordering.

ORDERING FORMAT / specify phase connection, factory orientation and any required cord length
Typical: PT225-S-10-DCXX-IGL2130C-IGL2130C-G-T
Reverse: PT225-S-10-DCXX-IGL2130C-IGL2130C-G-R

Certification reference - covered PT225 factory configurations. Intertek 5011082; Report 106508638CRT-001.

Illustrations not to scale. Body dimensions exclude projections and cord.