USA TrackBusway™ 30A Outlet Box

ETL Listed to UL 857 Busway Standards
by Intertek

Built in the United States

208V, three-phase per output / 2 x 3-pole / 2 x L15-30R receptacles

CATALOGUE NUMBER / FIXED CONFIGURATION + YOUR ORDER SELECTIONS


PT225-S-10-OB-L1530R-L1530R-G-[T/R]

Base configuration
Unit + receptacle shown below

Phase connection
L1 + L2 + L3 (fixed)

Factory orientation
Choose -T or -R


YOUR TAP-OFF CONFIGURATION



Enclosure views; connection detail at right

Supply	208V, three-phase per output
A Protection	2 x 30A, 3-pole breakers; one per output
B Output	2 x L15-30R receptacles
Grounding	Standard equipment ground
Enclosure	Standard S
Body W x H x D	13.280 x 14.620 x 3.860 in.
Required SCCR	Specify with order; subject to factory confirmation
Power monitoring	None

B OUTLET RECEPTACLE




L15-30R

30A, 250V AC device rating
Equipment ground included
No neutral contact

trackbusway.com/products/t225-3-pole-breakered-outlet-box

Phase connection / specify when ordering



T225 conductor arrangement

2 independent circuits; one 30A, 3-pole breaker per output.

Receptacle 1
30A / 3-pole breaker
L1 + L2 + L3


Receptacle 2
30A / 3-pole breaker
L1 + L2 + L3

PHASE CONNECTION = L1L2L3 (fixed)
Each output uses all three phases. No phase entry is required.

Each output uses all three phases through its own 3-pole breaker. Equipment ground is retained; neutral is included where specified.

CHOOSE THE FACTORY BREAKER ORIENTATION

Both views below show the breaker facing left. Enclosures continue below the break lines.




-T TYPICAL

CONDUCTORS / INSULATOR
LEFT side

BREAKER FACES LEFT

SAME SIDE
as the conductors



-R REVERSE

CONDUCTORS / INSULATOR
RIGHT side

BREAKER FACES LEFT

OPPOSITE SIDE
as the conductors

FACTORY-SET. NOT FIELD-ROTATABLE. Select -T or -R when ordering.

ORDERING FORMAT / specify phase connection, factory orientation and any required cord length
Typical: PT225-S-10-OB-L1530R-L1530R-G-T
Reverse: PT225-S-10-OB-L1530R-L1530R-G-R

Certification reference - covered PT225 factory configurations. Intertek 5011082; Report 106508638CRT-001.

Illustrations not to scale. Body dimensions exclude projections and cord.