
USA TrackBusway™

ETL Listed to UL 857 Busway Standards
by Intertek

20A T40 breakered outlet box

Built in the United States

240V | One L6-20R mounted receptacle



Supply	240V AC; line-to-line, single phase
Protection	One 20A two-pole breaker
Output	One L6-20R mounted receptacle
Conductors	Two lines and equipment ground; no neutral
Construction	Face-mounted output; no hanging cord



1 x L6-20R
Mounted receptacle

Contact detail; not to scale


Assembly shown in one finish. Available finish-specific catalogue numbers are listed below.

Catalogue numbers / available finishes

Finish	Standard
Galvanized	MD40-3-240-CB20-OB-ST-G
Black	MD40-3-240-CB20-OB-ST-B
White	MD40-3-240-CB20-OB-ST-W

G = galvanized; B = black; W = white. OB = outlet box. CB20 = breaker amperage. Existing output codes retained.

LINE-TO-LINE - 240V



Lower-deck A+B

Two lines and equipment ground; no neutral at this output.

One 20A two-pole breaker.

Standard A+B phase pair. Match the assembly to the stated supply voltage.

Original section drawing: Roman. Detailed wiring is linked below.

Product and configuration choices **Wiring & connection details (PDF)** **T40 listing information**