T40 selection & technical guide

T40 3-Phase PowerDrop Cord

Download a configuration sheet before selecting ordering options. Match the voltage, output type, quantity and protection to the required build.

208V | 20A | One L15-20C inline connector

One-page cut sheet (PDF) Wiring details (PDF)

208V | 30A | One L15-30C inline connector

One-page cut sheet (PDF) Wiring details (PDF)

120/208V | 20A | One L21-20C inline connector

One-page cut sheet (PDF) Wiring details (PDF)

120/208V | 30A | One L21-30C inline connector

One-page cut sheet (PDF) Wiring details (PDF)

480V | 20A | One L16-20C inline connector

One-page cut sheet (PDF) Wiring details (PDF)

480V | 30A | One L16-30C inline connector

One-page cut sheet (PDF) Wiring details (PDF)

277/480V | 20A | One L22-20C inline connector

One-page cut sheet (PDF) Wiring details (PDF)

277/480V | 30A | One L22-30C inline connector

One-page cut sheet (PDF) Wiring details (PDF)

Existing catalogue numbers

T40 3-Phase PowerDrop Cord

MD40-4-208-CB20-DC-XX-L1520C-G | L15-20 | 208V | No neutral / Galvanized

MD40-4-208-CB20-DC-XX-L1520C-B | L15-20 | 208V | No neutral / Black

MD40-4-208-CB20-DC-XX-L1520C-W | L15-20 | 208V | No neutral / White

MD40-4-208-CB30-DC-XX-L1530C-G | L15-30 | 208V | No neutral / Galvanized

MD40-4-208-CB30-DC-XX-L1530C-B | L15-30 | 208V | No neutral / Black

MD40-4-208-CB30-DC-XX-L1530C-W | L15-30 | 208V | No neutral / White

MD40-4-208-CB20-DC-XX-L2120C-G | L21-20 | 120/208V | With neutral / Galvanized

MD40-4-208-CB20-DC-XX-L2120C-B | L21-20 | 120/208V | With neutral / Black

MD40-4-208-CB20-DC-XX-L2120C-W | L21-20 | 120/208V | With neutral / White

MD40-4-208-CB30-DC-XX-L2130C-G | L21-30 | 120/208V | With neutral / Galvanized

MD40-4-208-CB30-DC-XX-L2130C-B | L21-30 | 120/208V | With neutral / Black

MD40-4-208-CB30-DC-XX-L2130C-W | L21-30 | 120/208V | With neutral / White

MD40-4-480-CB20-DC-XX-L1620C-G | L16-20 | 480V | No neutral / Galvanized

MD40-4-480-CB20-DC-XX-L1620C-B | L16-20 | 480V | No neutral / Black

MD40-4-480-CB20-DC-XX-L1620C-W | L16-20 | 480V | No neutral / White

MD40-4-480-CB30-DC-XX-L1630C-G | L16-30 | 480V | No neutral / Galvanized

MD40-4-480-CB30-DC-XX-L1630C-B | L16-30 | 480V | No neutral / Black

MD40-4-480-CB30-DC-XX-L1630C-W | L16-30 | 480V | No neutral / White

MD40-4-480-CB20-DC-XX-L2220C-G | L22-20 | 277/480V | With neutral / Galvanized

MD40-4-480-CB20-DC-XX-L2220C-B | L22-20 | 277/480V | With neutral / Black

MD40-4-480-CB20-DC-XX-L2220C-W | L22-20 | 277/480V | With neutral / White

MD40-4-480-CB30-DC-XX-L2230C-G | L22-30 | 277/480V | With neutral / Galvanized

MD40-4-480-CB30-DC-XX-L2230C-B | L22-30 | 277/480V | With neutral / Black

MD40-4-480-CB30-DC-XX-L2230C-W | L22-30 | 277/480V | With neutral / White

Connection and construction

T40 3-Phase PowerDrop Cord

Catalogue numbers and variant identities are retained. C identifies a female cord connector; R identifies a mounted receptacle. Existing ST/DT/SB/DS/Q codes remain valid.

PowerDrop cord-end boxes are used for duplex and quad straight-blade outputs. Other outputs use inline female connectors. Match the output count to the individual sheet.

120V single-circuit standard fittings flip between lower-deck A or B. Upper-deck C requires the separately ordered -WP configuration where offered. Double drops: Standard A+B; -WP supports A+C or B+C, with C supplied through the whip.

208V two-pole standard uses A+B; its optional -WP arrangement uses B+C. 240V two-pole standard uses A+B. Three-phase assemblies use lower-deck A+B and upper-deck C through the included whip.

The 40A busway rating does not replace the branch/device rating. Follow the selected sheet and marked-unit ratings. Unbreakered assemblies require appropriately rated upstream protection.

No enclosure dimensions are inferred from photographs. Project-specific top-mounted/bottom-fed whip arrangements are distinct from standard C-phase access.

T40 installation instructions (PDF)