T40 selection & technical guide

T40 120V Power Drop Cord

Download a configuration sheet before selecting ordering options. Match the voltage, output type, quantity and protection to the required build.

120V | 20A | One 5-20C inline connector

One-page cut sheet (PDF) **Wiring details (PDF)**

120V | 20A | One duplex 5-20R receptacle (2 outlets)

One-page cut sheet (PDF) **Wiring details (PDF)**

120V | 20A | Two duplexes (4 x 5-20R outlets)

One-page cut sheet (PDF) **Wiring details (PDF)**

120V | 15A | One L5-15C inline connector

One-page cut sheet (PDF) **Wiring details (PDF)**

120V | 20A | One L5-20C inline connector

One-page cut sheet (PDF) **Wiring details (PDF)**

120V | 15A | Two L5-15C inline connectors; two cords

One-page cut sheet (PDF) **Wiring details (PDF)**

Standard A+B; optional -WP supports A+C or B+C.

120V | 20A | Two L5-20C inline connectors; two cords

One-page cut sheet (PDF) **Wiring details (PDF)**

Standard A+B; optional -WP supports A+C or B+C.

120V | 20A | One GFCI duplex 5-20R receptacle

One-page cut sheet (PDF) **Wiring details (PDF)**

T40 configuration selection

T40 120V Power Drop Cord

120V | 20A | Two GFCI duplexes (4 x 5-20R outlets)

One-page cut sheet (PDF) **Wiring details (PDF)**

120V | 30A | One L5-30C inline connector

One-page cut sheet (PDF) **Wiring details (PDF)**

GFCI protection is at the receptacle assembly. Duplex: one standard 20A single-pole breaker supplies one GFCI duplex. Quad: one shared standard 20A single-pole breaker supplies two GFCI duplexes. Other outputs retain their specified inline connector assemblies.

Two-output twist-lock: two separate cords, two inline female connectors, and two separate single-pole breakers on different phases. Standard uses A+B without a whip. With -WP, C supplies one cord through the whip and the standard fitting selects A or B for the other: A+C or B+C.

Existing catalogue numbers

T40 120V Power Drop Cord

MD40-2-120-CB20-DC-XX-SB-G | 5-20r Single Straight Blade / A or B - Standard / Galvanized

MD40-2-120-CB20-DC-XX-SB-B | 5-20r Single Straight Blade / A or B - Standard / Black

MD40-2-120-CB20-DC-XX-W-SB | 5-20r Single Straight Blade / A or B - Standard / White

MD40-2-120-CB20-DC-XX-SB-G-WP | 5-20r Single Straight Blade / C - Whip / Galvanized

MD40-2-120-CB20-DC-XX-SB-B-WP | 5-20r Single Straight Blade / C - Whip / Black

MD40-2-120-CB20-DC-XX-W-SB-WP | 5-20r Single Straight Blade / C - Whip / White

MD40-2-120-CB20-DC-XX-G-DS | 5-20r Duplex Straight Blade / A or B - Standard / Galvanized

MD40-2-120-CB20-DC-XX-B-DS | 5-20r Duplex Straight Blade / A or B - Standard / Black

MD40-2-120-CB20-DC-XX-W-DS | 5-20r Duplex Straight Blade / A or B - Standard / White

MD40-2-120-CB20-DC-XX-G-DS-WP | 5-20r Duplex Straight Blade / C - Whip / Galvanized

MD40-2-120-CB20-DC-XX-B-DS-WP | 5-20r Duplex Straight Blade / C - Whip / Black

MD40-2-120-CB20-DC-XX-W-DS-WP | 5-20r Duplex Straight Blade / C - Whip / White

MD40-2-120-CB20-DC-XX-QS-G | 5-20r Quad Straight Blade / A or B - Standard / Galvanized

MD40-2-120-CB20-DC-XX-QS-B | 5-20r Quad Straight Blade / A or B - Standard / Black

MD40-2-120-CB20-DC-XX-QS-W | 5-20r Quad Straight Blade / A or B - Standard / White

MD40-2-120-CB20-DC-XX-QS-G-WP | 5-20r Quad Straight Blade / C - Whip / Galvanized

MD40-2-120-CB20-DC-XX-QS-B-WP | 5-20r Quad Straight Blade / C - Whip / Black

MD40-2-120-CB20-DC-XX-QS-W-WP | 5-20r Quad Straight Blade / C - Whip / White

MD40-2-120-CB15-DC-XX-G-ST | L5-15r Single Twist Lock / A or B - Standard / Galvanized

MD40-2-120-CB15-DC-XX-B-ST | L5-15r Single Twist Lock / A or B - Standard / Black

MD40-2-120-CB15-DC-XX-W-ST | L5-15r Single Twist Lock / A or B - Standard / White

MD40-2-120-CB15-DC-XX-G-ST-WP | L5-15r Single Twist Lock / C - Whip / Galvanized

MD40-2-120-CB15-DC-XX-B-ST-WP | L5-15r Single Twist Lock / C - Whip / Black

MD40-2-120-CB15-DC-XX-W-ST-WP | L5-15r Single Twist Lock / C - Whip / White

MD40-2-120-CB20-DC-XX-G-ST | L5-20r Single Twist Lock / A or B - Standard / Galvanized

MD40-2-120-CB20-DC-XX-B-ST | L5-20r Single Twist Lock / A or B - Standard / Black

MD40-2-120-CB20-DC-XX-W-ST | L5-20r Single Twist Lock / A or B - Standard / White

MD40-2-120-CB20-DC-XX-G-ST-WP | L5-20r Single Twist Lock / C - Whip / Galvanized

MD40-2-120-CB20-DC-XX-B-ST-WP | L5-20r Single Twist Lock / C - Whip / Black

MD40-2-120-CB20-DC-XX-W-ST-WP | L5-20r Single Twist Lock / C - Whip / White

MD40-2-120-CB15-DC-XX-G-DT | L5-15r Duplex Twist Lock / A+B - Standard / Galvanized

Existing catalogue numbers

T40 120V Power Drop Cord

MD40-2-120-CB15-DC-XX-B-DT | L5-15r Duplex Twist Lock / A+B - Standard / Black

MD40-2-120-CB15-DC-XX-DT-W | L5-15r Duplex Twist Lock / A+B - Standard / White

MD40-2-120-CB15-DC-XX-G-DT-WP | L5-15r Duplex Twist Lock / A+C or B+C - Whip / Galvanized

MD40-2-120-CB15-DC-XX-B-DT-WP | L5-15r Duplex Twist Lock / A+C or B+C - Whip / Black

MD40-2-120-CB15-DC-XX-DT-W-WP | L5-15r Duplex Twist Lock / A+C or B+C - Whip / White

MD40-2-120-CB20-DC-XX-DT-G | L5-20r Duplex Twist Lock / A+B - Standard / Galvanized

MD40-2-120-CB20-DC-XX-DT-B | L5-20r Duplex Twist Lock / A+B - Standard / Black

MD40-2-120-CB20-DC-XX-DT-W | L5-20r Duplex Twist Lock / A+B - Standard / White

MD40-2-120-CB20-DC-XX-DT-G-WP | L5-20r Duplex Twist Lock / A+C or B+C - Whip / Galvanized

MD40-2-120-CB20-DC-XX-DT-B-WP | L5-20r Duplex Twist Lock / A+C or B+C - Whip / Black

MD40-2-120-CB20-DC-XX-DT-W-WP | L5-20r Duplex Twist Lock / A+C or B+C - Whip / White

MD40-2-120-CB20-DC-XX-G-DGF | 5-20R GFCI duplex / A or B - Standard / Galvanized

MD40-2-120-CB20-DC-XX-B-DGF | 5-20R GFCI duplex / A or B - Standard / Black

MD40-2-120-CB20-DC-XX-W-DGF | 5-20R GFCI duplex / A or B - Standard / White

MD40-2-120-CB20-DC-XX-G-DGF-WP | 5-20R GFCI duplex / C - Whip / Galvanized

MD40-2-120-CB20-DC-XX-B-DGF-WP | 5-20R GFCI duplex / C - Whip / Black

MD40-2-120-CB20-DC-XX-W-DGF-WP | 5-20R GFCI duplex / C - Whip / White

MD40-2-120-CB20-DC-XX-G-QGF | 5-20R GFCI quad / A or B - Standard / Galvanized

MD40-2-120-CB20-DC-XX-B-QGF | 5-20R GFCI quad / A or B - Standard / Black

MD40-2-120-CB20-DC-XX-W-QGF | 5-20R GFCI quad / A or B - Standard / White

MD40-2-120-CB20-DC-XX-G-QGF-WP | 5-20R GFCI quad / C - Whip / Galvanized

MD40-2-120-CB20-DC-XX-B-QGF-WP | 5-20R GFCI quad / C - Whip / Black

MD40-2-120-CB20-DC-XX-W-QGF-WP | 5-20R GFCI quad / C - Whip / White

MD40-2-120-CB30-DC-XX-G-ST | L5-30r Single Twist Lock / A or B - Standard / Galvanized

MD40-2-120-CB30-DC-XX-B-ST | L5-30r Single Twist Lock / A or B - Standard / Black

MD40-2-120-CB30-DC-XX-W-ST | L5-30r Single Twist Lock / A or B - Standard / White

MD40-2-120-CB30-DC-XX-G-ST-WP | L5-30r Single Twist Lock / C - Whip / Galvanized

MD40-2-120-CB30-DC-XX-B-ST-WP | L5-30r Single Twist Lock / C - Whip / Black

MD40-2-120-CB30-DC-XX-W-ST-WP | L5-30r Single Twist Lock / C - Whip / White

Connection and construction

T40 120V Power Drop Cord

Catalogue numbers and variant identities are retained. C identifies a female cord connector; R identifies a mounted receptacle. Existing ST/DT/SB/DS/Q codes remain valid.

PowerDrop cord-end boxes are used for duplex and quad straight-blade outputs. Other outputs use inline female connectors. Match the output count to the individual sheet.

120V single-circuit standard fittings flip between lower-deck A or B. Upper-deck C requires the separately ordered -WP configuration where offered. Double drops: Standard A+B; -WP supports A+C or B+C, with C supplied through the whip.

208V two-pole standard uses A+B; its optional -WP arrangement uses B+C. 240V two-pole standard uses A+B. Three-phase assemblies use lower-deck A+B and upper-deck C through the included whip.

The 40A busway rating does not replace the branch/device rating. Follow the selected sheet and marked-unit ratings. Unbreakered assemblies require appropriately rated upstream protection.

No enclosure dimensions are inferred from photographs. Project-specific top-mounted/bottom-fed whip arrangements are distinct from standard C-phase access.

T40 installation instructions (PDF)